


AVANTAGE PRODUIT - PRODUCT ADVANTAGE
POTEAU 5 trous COMPLET, livré monté. Support de main courante orientable et réglable en hauteur (+30mm max)

Inoline, une ligne qui design votre maison. Ultra contemporaine, la ligne aéro-fuselée du garde-corps Inoline dessine et restructure architecturalement escaliers, mezzanines, terrasses, balcons...

5 drillings COMPLETE POST, supplied mounted. Swivelling and height adjustable handrail bracket (+30mm max)

Inoline, a line made to design your home. Ultra contemporary, the aerodynamic look of Inoline railings redesigns and restructures staircases, mezzanines, terraces, balconies.....

CARACTERISTIQUES TECHNIQUES - SPECIFICATIONS

dimensions hors tout
overall dimensions

poteau - post
35 x 55 x H 966 mm

platine au sol - floor fastened bracket
110 x 120 mm

support de main courante - handrail bracket
Ø14 x H 127 mm

MATIERE - MATERIAL

aluminium
corps poteau
post structure

fonte d'aluminium - cast aluminium
support main courante
handrail bracket

acier - steel
platine au sol + visserie
post bracket + fastenings

thermolaqué RAL9005 - powder coated RAL9005
corps poteau +support main courante + platine au sol
post structure + handrail bracket + floor post bracket

inox - stainless steel
visserie
fastenings

matière + traitement
material + treatment

traitement - finition
treatment - finishing

provenance
origin

Chine
China

LOGISTIQUE - LOGISTIC

gencod 3 443 440 008 002

livré
supplied

monté - mounted

conditionnement
packaging 1

colis
package

H 97,2 x L 12,5 x lg 11,3 cm

poids unité de vente
weight unit sale 2,77g

palette de transport
transport pallet

INFORMATIONS COMPLEMENTAIRES - OTHER INFORMATION

utilisation
use intérieure + extérieure
indoor + outdoor

autres informations
accessoires fournis

other informations
accessories supplied

Perçages platines au sol: Ø11mm (x4)
Ground mounting plate drillings: Ø11mm (x4)

Support de main courante intégré au poteau pivotant et réglable en hauteur (+30mm maxi).
Handrail support integrated to the post, rotating and adjustable height (+ 30mm max) .

Platine de fixation au sol intégrée au poteau.
Floor fastened bracket integrated to the post.

Règlementation:
L'entraxe poteaux ne doit pas dépasser 1000mm, accessoires de fixation inclus hors fixation au sol, à choisir selon la nature du sol.

Regulation:
The space between posts must not exceed 1000mm, mounting accessories included excluding floor mounting kits, to be selected according to the type of floor.

conseils installation
installation advice